



HARD PVC DONKERGRIJS RAL 7011
PVC RIGIDE GRIS FONCÉ RAL 7011
U-PVC DARK GREY RAL 7011

L = 5 m, gladde uitvoering
Volgens DIN 8061/62 , ISO/R161- 1960 , EN 15877
Zelfdovend volgens DIN 4102.
100% weekmakervrij, siliconenvrij, krijtvrij, regeneraatsvrij

L = 5 m, bouts lisses
Suivant DIN 8061/62 , ISO/R161- 1960 , EN 15877
Auto-extinguible selon DIN 4102
100% sans plastificateurs, silicones, graie et régénérats

L = 5 m, butt ends
According to DIN 8061/62 , ISO/R161- 1960 , EN 15877
Self-extinguishing according to DIN 4102
100% without plastifiers, silicones, crayon or regenerated plastics

REEKS SERIE SERIES	SDR 51			SDR 34.4			SDR 21			SDR 13.6			SDR 9		
	PN 4			PN 6			PN 10			PN 16			PN 16*		
D	s	KG/M	€/M	s	KG/M	€/M	s	KG/M	€/M	s	KG/M	€/M	s	KG/M	€/M
6													1.0	0.025	2.47
8													1.0	0.035	2.77
10													1.2	0.054	3.10
12													1.4	0.074	3.36
16										1.2	0.091	1.69	1.8	0.125	2.47
20										1.5	0.139	2.23	2.3	0.199	3.10
25							1.5	0.177	2.59	1.9	0.215	2.87	2.8	0.299	4.62
32							1.9	0.280	3.97	2.4	0.347	4.99	3.6	0.489	7.86
40							1.9	0.355	4.74	3.0	0.533	7.18	4.5	0.761	12.22
50				2.0	0.366	6.30	2.4	0.560	7.18	3.7	0.821	10.66	5.6	1.178	18.61
63				1.9	0.571	9.40	3.0	0.866	9.64	4.7	1.306	16.38	7.0	1.846	29.03
75	1.9	0.651	10.96	2.2	0.793	13.38	3.6	1.237	13.91	5.6	1.847	23.32	8.4	2.637	54.71
90	1.8	0.785	13.72	2.7	1.146	18.07	4.3	1.770	19.87	6.7	2.643	31.94	10.0	3.801	77.72
110	2.2	1.175	19.09	3.2	1.663	24.18	5.3	2.652	29.32	8.2	3.911	46.81	12.3	5.644	116.76
125	2.5	1.500	25.15	3.7	2.159	36.10	6.0	3.386	41.34	9.2	5.036	67.56			
140	2.8	1.863	31.99	4.1	2.691	42.79	6.7	4.237	47.83	10.3	6.304	81.02			
160	3.2	2.444	43.03	4.7	3.491	50.54	7.7	5.553	60.34	11.8	8.225	100.99			
180	3.6	3.064	58.39	5.3	4.432	79.09	8.6	6.974	88.20	13.3	10.435	138.74			
200	4.0	3.669	67.90	5.9	5.444	105.36	9.6	8.636	105.07						
225	4.5	4.667	89.70	6.6	6.855	105.55	10.8	10.908	125.76	16.6	16.242	207.28			
250	4.9	5.732	108.07	7.3	8.428	161.62	11.9	13.344	165.12						
280	5.5	7.214	139.91				13.4	16.838	190.51						
315	6.2	9.020	171.12	9.2	13.343	198.02	15.0	21.152	238.58						
355	7.0	11.400	231.36	10.4	16.955	270.48									
400	7.9	14.500	284.57	11.7	21.441	343.61									

PN 16* : versterkt / renforcé / reinforced

Andere lengten, kleuren en/of uiteinden op aanvraag
Autres longueurs, couleurs et/ou bouts sur demande
Other lengths, colours and/or ends on request