



HARD PVC DONKERGRIJS RAL 7011
PVC RIGIDE GRIS FONCÉ RAL 7011
U-PVC DARK GREY RAL 7011

L = 5 m, gladde uitvoering
Volgens DIN 8061/62 , ISO/R161- 1960 , EN 15877
Zelfdovend volgens DIN 4102.
100% weekmakervrij, siliconenvrij, krijtvrij, regeneraatvrij

L = 5 m, bouts lisses
Suivant DIN 8061/62 , ISO/R161- 1960 , EN 15877
Auto-extinguible selon DIN 4102
100% sans plastificateurs, silicones, graie et régénérats

L = 5 m, butt ends
According to DIN 8061/62 , ISO/R161- 1960 , EN 15877
Self-extinguishing according to DIN 4102
100% without plastifiers, silicones, crayon or regenerated plastics

REEKS SERIE SERIES	SDR 51			SDR 34.4			SDR 21			SDR 13.6			SDR 9		
	PN 4			PN 6			PN 10			PN 16			PN 16*		
D	s	KG/M	€/M	s	KG/M	€/M	s	KG/M	€/M	s	KG/M	€/M	s	KG/M	€/M
6													1.0	0.025	2.29
8													1.0	0.035	2.58
10													1.2	0.054	2.68
12													1.4	0.074	2.86
16										1.2	0.091	1.56	1.8	0.125	2.14
20										1.5	0.139	2.18	2.3	0.199	2.98
25							1.5	0.177	2.59	1.9	0.215	3.16	2.8	0.299	3.96
32							1.9	0.280	3.44	2.4	0.347	4.55	3.6	0.489	6.80
40							1.9	0.355	4.39	3.0	0.533	6.78	4.5	0.761	10.38
50				2.0	0.366	5.32	2.4	0.560	6.84	3.7	0.821	10.09	5.6	1.178	15.89
63				1.9	0.571	7.99	3.0	0.866	8.77	4.7	1.306	16.37	7.0	1.846	24.95
75	1.9	0.651	9.35	2.2	0.793	11.36	3.6	1.237	12.68	5.6	1.847	22.97	8.4	2.637	47.46
90	1.8	0.785	11.66	2.7	1.146	15.55	4.3	1.770	18.13	6.7	2.643	31.64	10.0	3.801	67.43
110	2.2	1.175	16.18	3.2	1.663	20.45	5.3	2.652	26.63	8.2	3.911	46.28	12.3	5.644	101.46
125	2.5	1.500	21.31	3.7	2.159	30.79	6.0	3.386	37.51	9.2	5.036	66.71			
140	2.8	1.863	27.36	4.1	2.691	36.41	6.7	4.237	43.42	10.3	6.304	80.41			
160	3.2	2.444	36.55	4.7	3.491	42.76	7.7	5.553	54.56	11.8	8.225	99.01			
180	3.6	3.064	49.90	5.3	4.432	67.61	8.6	6.974	84.08	13.3	10.435	137.87			
200	4.0	3.669	57.88	5.9	5.444	90.40	9.6	8.636	99.79						
225	4.5	4.667	76.67	6.6	6.855	90.65	10.8	10.908	114.49	16.6	16.242	205.70			
250	4.9	5.732	92.23	7.3	8.428	138.80	11.9	13.344	151.07						
280							13.4	16.838	175.08						
315	6.2	9.020	145.91	9.2	13.343	167.83	15.0	21.152	216.49						
355	7.0	11.400	189.73	10.4	16.955	232.33									
400	7.9	14.500	243.16	11.7	21.441	305.84									

PN 16* : versterkt / renforcé / reinforced

Andere lengten, kleuren en/of uiteinden op aanvraag
Autres longueurs, couleurs et/ou bouts sur demande
Other lengths, colours and/or ends on request